

DS-2DE2204IW-DE3(S6) 2 MP Network IR Mini PTZ Camera



Hikvision DS-2DE2204IW-DE3(S6) 2 MP Network IR Mini PTZ Camera can be widely used in multiple indoor scenes, such as malls, stores, factories, entrances and exits.

- High quality imaging with 2 MP resolution
- Clear imaging against strong back light due to 120 dB WDR technology
- 4× optical zoom provides close up views over expansive areas
- Hik-Connect cloud service and APP for remote management and views of devices
- Expansive night view with up to 30 m IR distance
- Built-in microphone and speaker



▪ Specification

| Camera Module | |
|-------------------------|---|
| Image Sensor | 1/2.8" progressive scan CMOS |
| Min. Illumination | Color: 0.05 Lux @ (F1.8, AGC ON); B/W: 0.005 Lux @ (F1.8, AGC ON); 0 Lux with IR |
| Shutter Speed | 1/1 to 1/30,000 s |
| Day & Night | ICR |
| Day/Night Switch | day, night, auto, scheduled-switch |
| BLC | yes |
| WDR | 120 dB WDR |
| HLC | yes |
| 3D DNR | yes |
| Defog | yes |
| Regional Exposure | yes |
| Image Settings | saturation, brightness, contrast, sharpness |
| Image Parameters Switch | yes |
| White Balance | Auto/Manual/ATW (Auto-tracking White Balance)/Indoor/Outdoor/Fluorescent Lamp/Sodium Lamp |
| Digital Zoom | 16 × |
| Privacy Mask | up to 24 masks (8 masks for each scene) |
| SNR | >52 dB |
| General Function | mirror, password protection, watermark, IP address filter |
| Lens | |
| Focal Length | 2.8 to 12 mm, 4 × Optical |
| Zoom Speed | Approx. 2 s (wide-tele) |
| FOV | Horizontal field of view: 96° to 46° (Wide-Tele) Vertical field of view: 51° to 26° (Wide-Tele) Diagonal field of view: 112° to 55° (Wide-Tele) |
| Aperture | F1.8 |
| PTZ | |
| Movement Range (Pan) | 350° |
| Movement Range (Tilt) | 0° to 90° |
| Pan Speed | pan speed: configurable from 0.1° to 60°/s; preset speed: 60°/s |
| Tilt Speed | tilt speed: configurable from 0.1° to 50°/s, preset speed 50°/s |
| Proportional Zoom | yes |
| Presets | 300 |
| Power-off Memory | yes |
| Park Action | preset, patrol scan |
| 3D Positioning | yes |
| PTZ Status Display | yes |
| Preset Freezing | yes |
| Scheduled Task | preset, dome reboot, dome adjust, aux output |
| Video | |
| Max. Resolution | 1920 × 1080 |
| Stream Type | main stream, sub-stream, third stream |

| | |
|-----------------------------|--|
| Main Stream | 50 Hz: 25 fps (1920 × 1080, 1280 × 960, 1280 × 720); 60 Hz: 30 fps (1920 × 1080, 1280 × 960, 1280 × 720) |
| Sub-Stream | 50 Hz: 25 fps (704 × 576, 640 × 480, 352 × 288); 60 Hz: 30 fps (704 × 480, 640 × 480, 352 × 240) |
| Third Stream | 50 Hz: 25 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288); 60 Hz: 30 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240) |
| Video Compression | H.265, H.264, MJPEG |
| H.264+ | yes |
| SVC | yes |
| ROI | yes |
| Audio | |
| Audio Compression | G.711alaw, G.711ulaw, G.722.1, G.726, MP2L2, AAC, PCM |
| Audio Bit rate | AAC: 16 kbps, 32 kbps, 64 kbps, MP2L2: 32 kbps, 40 kbps, 48 kbps, 56 kbps, 64 kbps, 80 kbps, 96 kbps, 112 kbps, 128 kbps, 144 kbps, 160 kbps, 192 kbps |
| Audio Sampling Rate | AAC: 16 kHz, 32 kHz, 48 kHz; MP2L2: 16 kHz, 32 kHz, 48 kHz; PCM: 8 kHz, 16 kHz, 32 kHz, 64 kHz |
| Environment Noise Filtering | yes |
| Smart Features | |
| Basic Event | motion detection, video tampering alarm, alarm input, alarm output, exception |
| Smart Event | intrusion detection, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection, audio exception detection |
| Smart Record | ANR, Dual-VCA |
| Smart Encoding | H.265+, H.264+, low bit rate, ROI, SVC |
| Network | |
| Network Storage | NAS (NFS, SMB/ CIFS) |
| Protocols | IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour, Websocket, Websockets |
| API | ISAPI, Hikvision SDK, Hik-Connect, ISUP, Open Network Video Interface (Profile S, Profile G, Profile T) |
| Simultaneous Live View | Up to 20 channels |
| User/Host | Up to 32 users. 3 levels: Administrator, Operator and User |
| Security Measures | User authentication (ID and PW), Host authentication (MAC address); HTTPS encryption; IEEE 802.1x port-based network access control; IP address filtering |
| Web Browser | IE10+, Chrome57+, Firefox52+, Safari12+ |
| Interface | |
| Communication Interface | RJ45, self-adaptive 10M/100M Ethernet port |
| On-board Storage | support microSD/microSDHC/microSDXC cards, up to 256 GB |
| Alarm Input | 1 alarm input |
| Alarm Output | 1 alarm output |
| Audio Input | 1 built-in microphone, 1 audio input, 2.0 to 2.4Vp-p, 1k Ohm±10% |
| Audio Output | 1 built-in speaker, 1 audio output, line level, impedance: 600 Ω |
| Power Output | 12 VDC, max. 60 mA |
| Supplement Light | |
| IR Distance | Up to 30 m |

| General | |
|-------------------------------|---|
| Power | 12 VDC, PoE (802.3at) |
| Power Consumption and Current | 14 W |
| Operating Conditions | Temperature: -10°C to 50°C (14°F to 122°F), Humidity: ≤ 90% |
| Reset | yes |
| Dimensions | Ø125 × 136.7 mm (Ø 4.92" × 5.38") |
| Weight | Approx. 650 g (1.4 lb.) |
| Approval | |
| Protection | IP54, 4000V Lightning Protection, Surge Protection and Voltage Transient Protection |

▪ Available Model

DS-2DE2204IW-DE3(S6)(B)


▪ Typical Application

Hikvision products are classified into three levels according to their anti-corrosion performance. Refer to the following description to choose for your using environment.

This model has NO SPECIFIC PROTECTION.

| Level | Description |
|------------------------|--|
| Top-level protection | Hikvision products at this level are equipped for use in areas where professional anti-corrosion protection is a must. Typical application scenarios include coastlines, docks, chemical plants, and more. |
| Moderate protection | Hikvision products at this level are equipped for use in areas with moderate anti-corrosion demands. Typical application scenarios include coastal areas about 2 kilometers (1.24 miles) away from coastlines, as well as areas affected by acid rain. |
| No specific protection | Hikvision products at this level are equipped for use in areas where no specific anti-corrosion protection is needed. |

▪ **Dimension**



▪ **Accessory**

▪ **Optional**

DS-1294ZJ



Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 [216]521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com